



COVIDIEN

positive results for life™

WarmTouch™ Convective Warming System.
Maintaining normothermia has never been so easy.



Covidien offers the **right solution**

The WarmTouch™ convective warming system provides veterinary clinicians with an easy solution to help maintain normothermia. The WarmTouch™ convective warming unit has an intuitive screen showing the temperature and status of each of the 5 temperature settings. The soft but strong WarmTouch™ blanket range is tailored for most surgical procedures, offering tear resistance, even airflow and patient comfort.



The innovative WarmTouch™ Convective Warming Unit

EASY TO USE

New intuitive LCD screen and menu function provide all information at a glance.

EASY TO CONTROL

5 different settings, including ambient and boost, for more flexibility and precision.

EASY TO HANDLE

The low weight makes it easy to transport and attach to a cart, bed rail or an IV pole.

EASY TO SERVICE

The onscreen filter expiration warning makes it easy to maintain and service.




WarmTouch™ Convective Warming Blankets: A distinctive design to optimize warming efficacy



The soft but strong WarmTouch quilted blankets meet a wide range of needs to offer the optimal solution in easy and effective patient warming.

Made of a strong two-ply material, they resist tears, punctures and fluids, yet are soft and flexible to allow custom draping and comfort for your patients.



- A** The fabric outer layer eliminates hot plastic surfaces that could make contact with the patient.
- B** Layered construction adds strength, so even minor punctures will not expand and cause the blanket to deflate.
- C** Specially positioned holes direct the airflow evenly onto the patient.

Warming with precision, handling with flexibility

A full range of blankets to accommodate a range of patients and procedures.



**WARMTOUCH™
FULL BODY
MULTI ACCESS
BLANKET**

Easy access to chest tubes, arteries and pulse checking.

5030810
25/CS

DIMENSIONS
Uninflated

40 in W x 79 in L
102 cm W x 201 cm L

Inflated
33 in W x 74 in L
84 cm W x 188 cm L



**WARMTOUCH™
UPPER BODY
BLANKET**

Dual inlets for added flexibility.

5030870
12/CS

DIMENSIONS
Uninflated

82 in W x 28 in L
208 cm W x 71 cm L

Inflated
72 in W x 24 in L
183 cm W x 61 cm L



**WARMTOUCH™
TORSO BLANKET**

Large side flaps to tuck underneath the patient. Dual inlets for added flexibility.

5030900
12/CS

DIMENSIONS
Uninflated

52 in W x 40 in L
132 cm W x 102 cm L

Inflated
44.5 in W x 36 in L
113 cm W x 91 cm L



**WARMTOUCH™
LOWER BODY
BLANKET**

Precise, localized warming with adjustable tape positioning.

5030880
12/CS

DIMENSIONS
Uninflated

41 in W x 56 in L
104 cm W x 142 cm L

Inflated
34 in W x 52 in L
86 cm W x 132 cm L



**WARMTOUCH™
CARDIAC
BLANKET
STERILE**

Unique design to minimize air distribution at patient's feet.

5030860
12/CS

DIMENSIONS
Uninflated

40 in W x 65 in L
102 cm W x 165 cm L

Inflated
34 in W x 53 in L
86 cm W x 135 cm L



**WARMTOUCH™
SURGICAL
ACCESS BLANKET
STERILE**

Sterile access to the surgical site.

5030890
12/CS

DIMENSIONS
Uninflated

40 in W x 79 in L
102 cm W x 201 cm L

Inflated
35 in W x 74 in L
89 cm W x 188 cm L



**WARMTOUCH™
PEDIATRIC
SURGICAL
BLANKET**

For over and under body use. Clear plastic head cover to maintain head temperature.

5030850
12/CS

DIMENSIONS
Uninflated

25 in W x 41 in L
63 cm W x 104 cm L

Inflated
22 in W x 35 in L
56 cm W x 89 cm L



**WARMTOUCH™
PEDIATRIC FULL
BODY BLANKET**

Easy access to chest tubes, arteries and pulse checking.

5030840
12/CS

DIMENSIONS
Uninflated

30 in W x 57 in L
76 cm W x 145 cm L

Inflated
27 in W x 49 in L
69 cm W x 124 cm L

WarmTouch™ Convective Warming System

ordering information and specifications

DESCRIPTION	SIZE	QUANTITY	CATALOG NUMBER
WARMTOUCH™ 6000 WARMING UNIT	24 in x 17 in x 12 in (60 cm x 43 cm x 30 cm) (hose fully collapsed, nozzle in storage position on unit)	1/box	5016000A

WARMING UNIT

Weight with Power Cord 5.2kg (11.5 pounds)

TRANSPORT CART (OPTIONAL)

Weight 3.1kg (6.8 pounds)
Height 67.1cm (26.4 inches)
Width 32.3cm (12.7 inches)
Depth 38.6cm (15.2 inches)

ELECTRICAL REQUIREMENTS ENVIRONMENTAL

Power Requirements 100 to 240 V AC
 Max. current at 100 V = 8 A
 Max. current at 240 V = 5 A

Input Frequency 50/60 Hz ±1 Hz

Fuse (x2) Littlefuse (mfr.) 0218010; 250 V, 10 A

Temperature 18°C to 28°C (64.4°F to 82.4°F)

PERFORMANCE SPECIFICATIONS

Maximum Contact Surface Temperature 44.1°C (111.4°F)

Average Time for Contact Surface Temperature to Rise from 23°C ±2°C to 37°C 6 minutes

Average Time for Temperature of Air Exiting the Hose to Rise from 23°C ±2°C to 37°C < 1 minute

Accuracy of Displayed Temperature ±1.0°C (air entering hose)

Automatic Temperature Stepdown (Boost to High Temperature) After 45 minutes of continuous use, blower will step down from the Boost to High setting.

Thermal Protection Threshold Thermostat (internal): 49°C to 55°C (120°F to 131°F)

Average Alarm Level 56 dB @ 1 meter

WarmTouch™ Convective Warming System.
Maintaining normothermia has never been so easy.



WarmTouch™
Lower Body Blanket



WarmTouch™
Convective Warming Unit





6135 GUNBARREL AVENUE
BOULDER, CO 80301
800-635-5267

COVIDIEN.COM/RMS

IMPORTANT: Please refer to the package insert for complete instructions, contraindications, warnings and precautions.

COVIDIEN, COVIDIEN with logo, Covidien logo and *positive results for life* are U.S. and internationally registered trademarks of Covidien AG. Other brands are trademarks of a Covidien company. © 2013, 2014 Covidien. 13-PM-0157(1)